



The Hammer/Beater Mill consists of a simple but sturdy overhung beater cross design with ease of accessibility and cleaning. The standard machine is of cast iron. The mill occupies minimal bench space. A 1.5kW motor drives a beater cross at 8,000rpm above a curved replaceable screen. In its new form the grinding chamber is mounted above the motor and the shaft is driven by means of a short-toothed belt.

THE BEATER CROSS

This consists of a four-armed cross that revolves at a high speed and shatters or tears anything fed in through the throat from the small hand-feed tray illustrated. Manufactured from a high-grade steel alloy, it is carefully treated to obtain maximum hardness and strength, and is constructed so that it can be reversed when the leading edges are worn.

THE SCREENS

The perforated plate-type screen is fitted in the bottom section of the grinding chamber, and this regulates the size of the ground product. With each machine two cast iron screen frames are supplied together with one each of eight perforated plate screens having hole diameters 0.8, 1.0, 1.25, 1.5, 2.0, and 3.0mm.



SAFETY

The arrangement has been specially designed to meet all the requirements of the UK Health and Safety at Work Act.

An electrically interlocked door, which must be opened in order to change the screens or to remove the collecting bag, disconnects the current. It is impossible to start the machine until this door has been closed.

The inlet throat has been extended to prevent accidental injury to fingers as it is not possible to reach inside the grinding chamber.

To assist with cleaning, the front casing is fitted with a specially designed hinge so that the front can be dropped without the need to lift it away from the body of the machine.

BEARINGS

Roller and ball bearings are enclosed in a suitable housing and lubricated with high-speed grease, are of ample size to give trouble-free running over long periods.

GROUND SAMPLE COLLECTING SYSTEM

For general laboratory grinding, the mill is supplied with bag collection. This is detachable from the metal frame which is clipped with the bag to the underside of the mill, and serves the dual purpose of collector and air filter.

REQUIREMENTS

Electrical supply:

FT2-A: 220-240V / 1ph / 50Hz

FT2-F: 220V / 3ph / 60Hz

OVERALL DIMENSIONS

Height: 0.682m

Width: 0.414m

Depth: 0.765m

SHIPPING SPECIFICATION

Volume: 0.45m³

Gross weight: 120kg

ORDERING CODES

FT2-A: 220-240V / 1ph / 50Hz

FT2-F: 220V / 3ph / 60Hz

ORDERING SPECIFICATION

- A self-contained mill using a reversible, high-grade steel beater cross
- Supplied with perforated plate screens ranging from 0.8mm to 3.0mm
- Fitted with a 1.5kW motor giving operating speeds of 8,000rpm via a toothed belt
- The unit is supplied with a detachable collection bag
- Front case is simply lowered for easy cleaning
- Safe design prevents accidental access of fingers, and the door is electronically interlocked



Head Office:
Armfield Limited
Bridge House, West Street,
Ringwood, Hampshire
BH24 1DY England

Telephone: +44 1425 478781
Fax: +44 1425 470916
E-mail: sales@armfield.co.uk

U.S. Office:
Armfield Inc.
9 Trenton - Lakewood Road
Clarksburg NJ 08510
Tel/Fax: (609) 208-2800
E-mail: info@armfieldinc.com

© 2016 Armfield Ltd. All Rights Reserved
We reserve the right to amend these specifications without prior notice. E&OE 03/14/3k
Correct at time of going to press.



armfield

Innovators in Engineering Teaching Equipment

learn more! www.armfield.co.uk



Scan for website

