

**FT18 REVERSE OSMOSIS/ULTRAFILTRATION UNIT**



Miniature-scale research & development technology

*The Armfield RO/UF unit is the smallest known industrial membrane system of its type in the world. It is designed specifically for laboratory scale testing of both reverse osmosis and ultrafiltration techniques.*

**features**

- Dual operation, RO/UF
- Uses proprietary membranes available from PCI
- Clean-in-place facility
- Mobile and self-contained operation
- Computer linked for data logging and analysis

**benefits**

- Rapid changeover from RO to UF and back
- Easily cleaned and maintained

**armfield**  
TOTAL R&D SOLUTIONS



## EXPLORE WITH armfield

Miniature-scale R & D technology

Armfield R&D products include:

316 Stainless steel



CE certification



Extended warranty as standard



For more product information please visit:  
[www.explorearmfield.com](http://www.explorearmfield.com)



SCAN QR CODE

\*Scan for website

\* Scan with mobile smartphone with QR code scanning software installed.



An ISO 9001 Company

### Head Office:

Armfield Limited  
Bridge House, West Street,  
Ringwood, Hampshire.  
BH24 1DY England

Telephone: +44 1425 478781  
Fax: +44 1425 470916  
E-mail: [sales@armfield.co.uk](mailto:sales@armfield.co.uk)

### U.S. Office:

Armfield Inc.  
436 West Commodore Blvd (#2)  
Jackson, NJ 08527  
Telephone: (732) 928 3332  
Fax: (732) 928 3542  
E-mail: [info@armfieldinc.com](mailto:info@armfieldinc.com)

follow us



[twitter.com/Armfield\\_IFT](https://twitter.com/Armfield_IFT)  
[facebook.com/Armfielduk](https://facebook.com/Armfielduk)  
[linkedin.com/companies/armfield-limited](https://linkedin.com/companies/armfield-limited)  
[youtube.com/user/armfieldUK](https://youtube.com/user/armfieldUK)  
[explorearmfield.wordpress.com](https://explorearmfield.wordpress.com)

0712/3k/S02995

## Description

The FT18 is fully self-contained in a mobile cabinet. Comprehensive instrumentation is provided with digital meters displaying temperatures and system pressure. In addition to the membrane module, the cabinet also houses feed and permeate tanks, a plate heat exchanger and positive displacement pumps. Connection to cooling water and a suitable electrical supply is all that is required for normal operation.

All parts in contact with the process fluid are constructed from hygienic design materials such as stainless steel, PTFE and silicone rubber.

The RO/UF unit has an efficient clean-in-place facility and is easily dismantled for servicing or maintenance.

It uses a PCI MICRO 240 membrane module which accommodates all PCI membrane types. The unit is supplied with a pack of both R.O. membranes (AFC99) and U.F. membranes (ES625)

(other membranes not supplied by Armfield).

Membranes can be installed or removed rapidly for use in either process.

The filtration membranes differ only in length and quantity from those installed in the full-scale plant. Using small quantities of process fluid, operating parameters can be established and then optimised to effect a confident transition to full-scale.

## APPLICATIONS

- Concentration/clarification/fractionation and standardisation of:
  - > milk
  - > whey
  - > fruit juices
  - > vegetable juices
  - > alcoholic beverages
- Treatment of effluent
- Enzymes, antibiotics and organic acids



Removing the membrane from the module

*\*PCI invites contact regarding membrane information and can provide details of local suppliers:*

**Tel: +44 (0) 1256 303800 Fax: 44 (0) 1256 303801**

## Specifications

Flowrates:	30, 18, 15 and 9lpm
Pressures:	Variable up to 55 bar
PCI MICRO-240 Membrane Module suitable for two PCI* membranes	
Diameter:	1.25cm
Area:	0.024m <sup>2</sup>
Tubeside volume:	75ml
Typical permeate flow:	5-50ml/min
Feed tank capacity:	15 litres
Permeate tank capacity:	15 litres

## Requirements

Electrical Supply: Three Phase (see Ordering Codes)

Water supply: 10 lpm @ 12°C: a normal laboratory cold water supply will suffice.

## Ordering Codes

FT18-C:	415V/3ph/50Hz
FT18-D:	208V/3ph/60Hz
FT18-E:	380V/3ph/50Hz
FT18-F:	220V/3ph/60Hz
(all units 2.2kW)	

## Optional Accessories

FT18-90IFD-USB: Data Logging Accessory

Requires user supplied PC with USB interface running Windows XP or later.

FT18-15: Splash screen

## Shipping specification

Volume:	1.4 m <sup>3</sup>
Gross weight:	220kg

## Overall dimensions

Height:	1.1m
Width:	0.7m
Depth:	0.7m

The Armfield range includes HTST/UHT/aseptic systems, carbonator/filler/cappers, spray dryers/chillers, multifunction batch processors, ice cream freezers, margarine crystallisers, extractors, edible oils processors and more. For further information about our products and services, or to book a trial at one of our trials facilities, please contact us.

[www.explorearmfield.com](http://www.explorearmfield.com)